

# INT-TX Integrus

www.boschsecurity.com.cn



u                    4 8 16 32  
 u                    DCN                    CCS 900  
 u  
 u                    /

## Integrus



- 
- 
- /
- 
- 
- 
- 
- 
- /
- DCN
- DCN
- 19 (2U)
- 

- 2 x 16 LCD
- /
- 



- 
- H 15
- LBB 3422/20
- 4 8 16 32
- 2 XLR

- 1
- 3.5 0.14

- 1 BNC HF
- 6 BNC HF 30
- 2 DCN \*

\* LBB 4416/xx



1 INT-TX Integrus

1 19

1

1



	100-240Vac	50-60Hz
	55W	
	29W	
	+3dBV (± 6dB)	+6dBV
	+15dBV (± 6dB)	+18dBV
	+6	+18dBV
	32	2
HF	1 Vpp	10mVpp
HF	75	
HF	1 Vpp	6VDC 75

x	x	
	92x440x410	3.6x17.3x16.1
19	88x483x410	3.5x19x16.1
	40	1.6
	370	14.6
	6.8	15.0

	19
	(PH10736)



**INT-TX04 4**

Integrus 4

**INT-TX04**

**INT-TX08 8**

Integrus 8

**INT-TX08**

**INT-TX16 16**

Integrus 16

**INT-TX16**

**INT-TX32 32**

Integrus 32

**INT-TX32**

**INT-TX04-US 4**

**(US)**

Integrus 4

**INT-TX04-US**

**INT-TX08-US 8**

**(US)**

Integrus 8

**INT-TX08-US**

**INT-TX16-US 16**

**(US)**

Integrus 16

**INT-TX16-US**

**INT-TX32-US 32**

**(US)**

Integrus 32


**INT-TX32-US**

**LBB 3422/20**

CCS 900

**LBB3422/20**

Integrus  
LBB 3222/04 6



333  
: 200335  
: +86 21 22181111  
: +86 21 22182388  
www.boschsecurity.com.cn

11 5  
506-509  
: +852 2635 2815  
: +852 2648 7986  
www.boschsecurity.com.cn