

# SHURE®

LEGENDARY  
PERFORMANCE™

SHURE  
UA846Z2

GLX-D Frequency Manager

SHURE  
GLXD4R



SHURE  
GLXD4R



SHURE  
GLXD4R



SHURE  
GLXD4R



SHURE  
GLXD4R



SHURE  
GLXD4R



GLX-D® ADVANCED



# GLX-D® Advanced

## GLX-D ADVANCED

UA846Z2 GLX-D



/

GLXD4R  
2.4 GH

GLXD4R

LED

LCD

XLR



GLXD1  
GLXD2

GLXD4R

GLXD1  
GLXD2

SM58

30  
20  
16

60  
50



GLX-D A

GLX-D

1. GLX-D

GLXD4R

2.4 GH



2. GLX-D

( 11 )

9

A

GLX-D



PA805Z2-RSMA

8 B

2.4GH

24 B



UA505

PA805Z2-RSMA UA8-Z2



RSMA

50

6 25 50 100





GLX-D A

	UA846Z2	GLXD4R	PA805Z2-RSMA
9 11	15 VDC	42 197 163 ( )	<2.1 (VSWR) 2050 2700 MH
30 (100 ) 60 (200 ) 20 (65 ) 50 (165 )	15 VDC ( 6)	907.2	(2.45 GH ) 8 B
GLX-D	18 C 63 C(0 F 145 F)	14 18 VDC( )550 A	<b>3 dB</b> 100
20 H 20 H	45 483 192 ( )	>35 B( )	(2.45 GHz ) 89%
120 B A	1.63	18 42 B(1 B )	50
1 /A 4.0 2 3 4 /B 7.3	SMA	/ 30 B	(2.45 GHz ) 24 B
-88 B ( )	2400 2483.5 MH	50	SMA
0.2%( )	35 B( )	20 B	105 164 27.5 ( )
10 W E.I.R.P.( )	50		70
18 C(0 F) 57 C(135 F)	10 B		
29 C( 20 F) 74 C(165 F)	+15 B		
( ) 3)	WA302 SMA 2400 2483.5 MH (OIP3) 48 B ( )		
16	50		
/	35 B( )		
	3 0 B		

		<b>6.35</b> (1/4 )
	100	100 (50 )
	+18 BV 12 BV	+12 BV
	1= 2= 3=	= = =

**GLXD1**

90.4 64.5 22.9  
( )  
3.7 V  
(1 H 1% )+  
8.4 BV (7.5 V - )  
900  
10 W E.I.R.P.( )  
4 (TA4M)

TA4M  
1 ( )  
2 +5 V  
3  
4  
( 4 )

**GLXD2**

(SM58)  
252 51  
( )  
(SM58 )  
267  
3.7 V  
10 W E.I.R.P.( )  
145 B SPL



625 22  
info@shure.com.hk

618  
(II) 18 A  
info@shure.com.cn

1  
816