

HU

®

SHURE
UA846Z2

GLX-D Frequency Manager

POWER

SHURE
GLXD4R

SHURE GLXD4R control panel for channel A1. Includes a digital display showing "A1 15.52 -20", a "channel" selector, and a "mute" button.

SHURE
GLXD4R

SHURE GLXD4R control panel for channel A2. Includes a digital display showing "A2 12.39 -20", a "channel" selector, and a "mute" button.

SHURE
GLXD4R

SHURE GLXD4R control panel for channel A3. Includes a digital display showing "A3 15.55 -20", a "channel" selector, and a "mute" button. A hand is pointing at the "channel" selector.

SHURE
GLXD4R

SHURE GLXD4R control panel for channel A4. Includes a digital display showing "A4 09.20 -20", a "channel" selector, and a "mute" button.

SHURE
GLXD4R

SHURE GLXD4R control panel for channel A5. Includes a digital display showing "A5 15.51 -20", a "channel" selector, and a "mute" button.

SHURE
GLXD4R

SHURE GLXD4R control panel for channel A6. Includes a digital display showing "A6 11.43 -20", a "channel" selector, and a "mute" button.

GLX-D® ADVANCED



GLX-D® Advanced

GLX-D ADVANCED

UA846Z2 GLX-D



/

2.4 GH GLXD4R

GLXD4R

LED

LCD

XLR



GLXD1
GLXD2

GLXD4R

GLXD1
GLXD2

SM58

30
20
16

60
50



GLX-D A

GLX-D

1. GLX-D

GLXD4R

2.4 GH



2. GLX-D

(11)

A

9

GLX-D



PA805Z2-RSMA

8 B

2.4GH

24 B



UA505

PA805Z2-RSMA UA8-Z2



RSMA

50

6 25 50 100

3.

GLX-D

4.

GLX-D

USB



16





GLX-D A

	UA846Z2	GLXD4R	PA805Z2-RSMA
9 11	15 VDC	42 197 163 ()	<2.1 (VSWR) 2050 2700 MH
30 (100) 60 (200) 20 (65) 50 (165)	15 VDC (6)	907.2	(2.45 GH) 8 B
GLX-D	18 C 63 C(0 F 145 F)	14 18 VDC()550 A	3 dB 100
20 H 20 H	45 483 192 ()	>35 B()	(2.45 GHz) 89%
120 B A	1.63	18 42 B(1 B)	50
1 /A 4.0 2 3 4 /B 7.3	SMA	/ 30 B	(2.45 GHz) 24 B
-88 B ()	2400 2483.5 MH	50	SMA
0.2%()	35 B()	20 B	105 164 27.5 ()
10 W E.I.R.P.()	50		70
18 C(0 F) 57 C(135 F)	10 B		
29 C(20 F) 74 C(165 F)	+15 B		
() 3)	WA302 SMA 2400 2483.5 MH (OIP3) 48 B ()		
16	50		
/	35 B()		
	3 0 B		

		6.35 (1/4)
	100	100 (50)
	+18 BV 12 BV	+12 BV
	1= 2= 3=	= = =

GLXD1

90.4 64.5 22.9 ()	(1 H 1%)+
3.7 V	8.4 BV (7.5 V -)
900	TA4M
10 W E.I.R.P.()	1 () 2 +5V 3 4
4 (TA4M)	(4)

GLXD2

(SM58)	10 W E.I.R.P.()
252 51 ()	145 B SPL
(SM58)	
267	
3.7 V	