


VPX725

15"

- ▶ 15"
- ▶ 1.5"
- ▶
- ▶ 70° × 60° (H × V)

DuraFlex™

- ▶ 16
- ▶ 12



VPX725
15"

VPX725 1.5" JBL 2408H-1

15"

15"

70° × 60° (H × V)

VPX725
12

VPX725

VPX725
DuraFlex™
VPX725

16

	(-10 dB) ¹	40 Hz - 20 kHz
	(±3 dB) ¹	60 Hz - 20 kHz
		70° × 60° (H × V)
		1.9 kHz
	¹	900 W/1800 W/3600 W (/ /)
	(1w@1m) ²	100 dB
		4 Ohms
	³	130 dB (136 dB)
		2 × 15" (381.00 mm)
		1 × JBL 2408H-1
		15/18 mm
		12 × (3@ 3@ 2@ 2@) M10
		2 ×
		DuraFlex™
		16
		2 × Neutrik®Speakon®NL-4
	(H × W × D)	1244 mm × 535 mm × 459 mm (49.0 in × 21.1 in × 18.1 in)
		44.86 Kg (98.90 lbs)

¹ IEC 6 dB ²
² (4)
³

▶ VPX725 15"

mm

Δ	Δ
12388	12439
∇	∇



JBL Professional
8500 Balboa Boulevard, P.O. Box 2200
Northridge, California 91329 U.S.A.
© Copyright 2018 JBL Professional
www.jblpro.com

VPX725
SZ
26/01/18