

Preliminary

Confidea DV G3

Generation III

WIRELESS DELEGATE VOTING UNIT

Art. 71.98.0006



Confidea DV G3

OLED

RFID

RFID

Confidea

Confidea®

Confidea "Smart Power Management"

Confidea

Confidea

AES

Confidea DV G3

4h : 1 Hz
 2h : 2 Hz
 1h : 4 Hz

LED

LED



:
:
:

LED + 2 LED

Confidea

OLED				
				16 bit digital @ 32 kHz
				max 3.5W
	LED		RF	< 20 dBm
				23 ms
				(D-MIC 30,40, 50SL)
				单向性
RFID				-43.4 dBV/Pa
				130 Hz - 15kHz
				680
D - MIC30SL		71.98.0053		
D - MIC40SL		71.98.0054		
				150 - 20 000 Hz
D - MIC50SL		71.98.0055		
Confidea BP		71.98.0042		OLED 128 x 64
				5mm
Confidea CHT		71.98.0043		
Confidea CHC		71.98.0044		80 mW/ 32
				77.5 dB (A)
TEL151		71.04.0151		100 - 14 000 Hz
CoCon				> 16
CoCon		71.98.1101		
CoCon			THD+N	0.06 % @ 1kHz in 32 load
CoCon		71.98.1104		
CoCon				
CoCon		71.98.1102		
				+5 ... 50 °C
RFID				
		71.43.2001		
RFID				
		71.43.2002		230(w), 130(h), 60(d)
			(g)	480
				RAL9011
3.5 mm jack				Confidea DV G3 71.98.0006

